



PREMIUM ACRYLIC TEXTURE COATING

One Coating Does It All

- Use as self-priming base coat & texture coat
- Saves time, materials & costs

Unsurpassed Durability

- Reinforced with titanium & marble

Impact Resistant

- Five times harder than standard texture & paint

Flexible

- Resists stress cracking

Scrubbable

- Ideal for heavy traffic areas
- Won't re-emulsify even when cleaned with heavy duty chemicals

5-Year Mold & Mildew Protection Guarantee

- Mildew-proof* - contains Roman's exclusive Mildew Guard™ Mildewcide System to protect coated surfaces



ARMORTEX
Deep Tint Base
#56005 - 5 Gal.

ARMORTEX
Roman White/
Tint Base
#51100 - 5 Gal.



*Setting the standard
for durable mildew-proof
texture finish systems*

www.romanarchitecturalfinishes.com

* This product contains a mildewcide that protects the coating film only.





A unique self-priming texture & finish coating in one!

ARMORTEX™ Premium Acrylic Texture Coating is formulated with titanium and marble and provides unsurpassed rugged durability for interior wall surfaces.

Long lasting texture finishes unparalleled in the industry.



- Unlike other textures that have limited use in moist atmospheres, **ARMORTEX** contains Roman's exclusive **MILDEW GUARD™** and can be used where mold and mildew is a concern.
- Available in 12 standard colors or can be custom tinted.
- Invisible, quick touch-up for maintenance staff
- Ink, marker & scuff marks easily removed with "Mr. Clean® Magic Eraser®"
- Complete **Care and Maintenance Booklet** provided to staff

SPECIFICATIONS

Mold Resistance	Mildew-proof*	Coverage	ARMORTEX Base Coat: Up to 110 sq. ft./gal. @ 8 mil wet. ARMORTEX Top Coat: Up to 125 sq. ft./gal. for orange peel & knockdown
Scrubable	Passes 2500 scrub cycles.	Adhesion	Superior adhesion to bare drywall, cured plaster, paint, texture, wood paneling and masonry.
VOC	VOC compliant. Meets AIM, CARB, OTC and SCAQMD requirements.	Recommended Uses	New or existing construction.
Tintable	To any medium hue or pastel tone.	Dry Time/Clean Up	Dries to the touch in 1-2 hours, may vary based on mil thickness, humidity & temperature. Easy soap and water clean up.

For more information contact
Roman Customer Service at 800-488-6117.

