

## Product Data Sheet

## TEKNAgrip®, PRO-505

**Product Numbers:** 09305, 09301, 09312

**Base:** Modified starch

**General Properties:** TEKNAgrip®, PRO-505 is an activator for pre-pasted wallpaper. Designed to assist the retail customer in having a better wallpaper hanging experience. Saves the professional time and money.

- Added holding power
- Eliminates messy water soaking
- Longer open time to match patterns
- Minimizes seam separation
- Low VOC, LEED and VOC regulation compliant

**Recommended Uses:** For pre-pasted wallcoverings and for pre-pasted borders on primed surfaces.

**Compatible Coatings:** All ROMAN® primers

**Substrates:** Apply over a ROMAN® primer, such as VINYL PREP® or ULTRA PRIME®.

**Not Recommended For:** Existing vinyl wallcovering, bare drywall, or extremely rough surfaces such as concrete block or stucco

### SPECIFICATION DATA

**Percent Solids:** Approximately 3%

**Coverage:** Approximately 360 square feet per gallon

**Viscosity:** Approximately 4,700 cps

**VOC:** Less than 16 grams/liter

**Drying Time:** Drying time will vary depending on the temperature, ventilation and humidity of the room.

**Storage:** Avoid freezing; keep in cool, dry place.

### LIMITED WARRANTY

Roman warrants that it will replace this product free of charge if within 24 months of manufacture it is found defective in material or workmanship. This warranty is in lieu of any other. The exclusive remedy is limited to the replacement of the product and Roman disclaims all liability for consequential damages. Conditions of use are beyond our control.

Roman Decorating Products • Calumet City, Illinois  
Questions? Call 1-800-488-6117.

www.romandecoratingproducts.com

7/09



### APPLICATION INSTRUCTIONS

**Surface Preparation:** Surface must be free from grease and other residues, dry, smooth and structurally sound. Check surfaces for paint bonding, loose wallcoverings, damaged wallboard or plaster. Repair all unsound surfaces. Prime all surfaces (including oil-based coatings) with an acrylic primer, such as ROMAN® VINYL PREP® or ULTRA PRIME®. Before proceeding with any unusual conditions, consult your adhesive or wallcovering supplier.

**Tinting:** N/A

**Dilution:** Do not dilute.

**Application Method:** Use only when the room temperature is above 50°F. Apply an even coat of activator with a pasting machine, brush or roller. Book according to the wallcovering manufacturer's instructions.

**Drying Time:** Varies depending on the temperature, ventilation and humidity of the room.

**Clean-Up:** Before the activator dries, remove the excess with clean water.

### CAUTION

Do not freeze. Do not take internally. In case of ingestion, seek medical attention. Avoid contact with skin and eyes. Use of skin and eye protection is recommended at all times. If contact with eye occurs, flush with water for 15 minutes. If skin contact occurs, wash with soap and water. Seek medical attention if rash or other symptoms occur. Do not mix with other chemicals. Use in a well ventilated work area. Close container after each use. Keep out of reach of children.