

Product Data Sheet

Border Adhesive For Hanging Over Wallcoverings, PRO 525

Product Numbers: 12001, 12014

Base: Synthetic Polymer

General Properties: Border Adhesive For Hanging Over Wallcoverings, PRO-525 is a high tack adhesive designed specifically for hanging borders over vinyl. It is more suitable for hanging borders than regular vinyl over vinyl products.

- Provides tight bond of edges/seams
- No priming or sizing required
- Low VOC, LEED and VOC regulation compliant

Recommended Uses: For hanging pre-pasted and unpasted borders over vinyl wallcovering.

Not Recommended For: Bare Drywall, extremely rough surfaces such as concrete block, stucco and other rough surfaces.

Substrates: Existing vinyl wallcovering

Non-Compatible Coatings: Teflon or Tedlar Type Surfaces



SPECIFICATION DATA

Percent Solids: Approximately 9%

Coverage: Approximately 250 square feet per gallon

Viscosity: Approximately 24,000 cps

VOC: Less than 230 grams/liter

Drying Time: Drying time will vary depending on the temperature and humidity of the room.

Storage: Avoid freezing; keep in cool, dry place.

LIMITED WARRANTY

Roman warrants that it will replace this product free of charge if within 24 months of manufacture it is found defective in material or workmanship. This warranty is in lieu of any other. The exclusive remedy is limited to the replacement of the product and Roman disclaims all liability for consequential damages. Conditions of use are beyond our control.

Roman Decorating Products • Calumet City, Illinois
Questions? Call 1-800-488-6117.
www.romandecoratingproducts.com

7/09

APPLICATION INSTRUCTIONS

Surface Preparation: Surface must be free from grease and other residues, dry, smooth and structurally sound. Check surfaces for loose wallcoverings. Repair all unsound surfaces. Before proceeding with any unusual conditions, consult your adhesive or wallcovering supplier.

Tinting: N/A

Dilution: Do not dilute.

Application Method: Use only when the room temperature is above 50°F. For best results, moisten the back of pre-pasted borders with a damp sponge. Apply an even coat covering the entire surface. **IMPORTANT:** A thick coat is less effective than a thin coat. Avoid contact with the front of border.

Drying Time: Drying time between two vinyls will vary depending on the temperature and humidity of the room.

Clean-Up: Before the adhesive dries, remove excess with warm, clean water. Additional effort may be required if the adhesive is allowed to contact the surface of embossed or textured vinyls. The adhesive can be difficult to clean up when it is dry.

CAUTION

Do not freeze. Do not take internally. In case of ingestion, seek medical attention. Avoid contact with skin and eyes. Use of skin and eye protection is recommended at all times. If contact with eye occurs, flush with water for 15 minutes. If skin contact occurs, wash with soap and water. Seek medical attention if rash or other symptoms occur. Do not mix with other chemicals. Use in a well ventilated work area. Close container after each use. Keep out of reach of children.