

Product Data Sheet

VOV, PRO-555

Product Numbers:

Base: Modified starch and synthetic polymer

General Properties: VOV, PRO-555 is a high tack, low moisture adhesive for hanging new vinyl over existing vinyl. Use BORDER ADHESIVE FOR HANGING OVER VINYL, PRO-525 for hanging borders over vinyl.

- Maximum Adhesion
- Eliminates Priming/Sizing
- Excellent Slip and Open Time
- Low VOC, Leed and VOC regulation compliant

Recommended Uses: For vinyl over vinyl applications

Compatible Coatings: N/A

Substrates: Clean, dry, firmly attached vinyl wallcoverings. On existing heavily embossed wallcoverings, VOV should be applied to both the existing and new vinyl. (VOV on existing vinyl must dry for one hour before hanging new vinyl)

Not Recommended For: For pre-pasted wallpaper, borders or hanging over existing wallcovering that is Tedlar or Teflon coated



APPLICATION INSTRUCTIONS

Surface Preparation: Surface must be free from grease and other residues, dry, smooth and structurally sound. Be certain existing wallcovering is firmly attached to the wall. Be sure to repair or remove all loose wallcoverings. Before proceeding with any unusual conditions, consult your adhesive or wallcovering supplier.

Tinting: N/A

Dilution: Do not dilute.

Application Method: Use only when the room temperature is above 50°F. Apply a thin, even coat of adhesive.

IMPORTANT: A thick coat is less effective than a thin coat. Avoid contact with the surface of embossed, textured or delicate wallcoverings. On existing heavily embossed wallcovering, VOV should be applied to both the existing and the new vinyl.

Drying Time: Drying time between two vinyls will vary depending on the temperature, ventilation and humidity of the room.

Clean-Up: Before the adhesive dries, remove the excess with clean water. Additional effort may be required if the adhesive is allowed to contact the surface of embossed or textured vinyls. The adhesive can be difficult to clean up after it dries.

SPECIFICATION DATA

Percent Solids: Approximately 59%

Coverage: Approximately 160 square feet per gallon

Viscosity: Approximately 17,000 cps

VOC: Less than 15 grams/liter

Drying Time: Drying time will vary depending on the temperature, ventilation and humidity of the room.

Storage: Avoid freezing; keep in cool, dry place.

LIMITED WARRANTY

Roman warrants that it will replace this product free of charge if within 24 months of manufacture it is found defective in material or workmanship. This warranty is in lieu of any other. The exclusive remedy is limited to the replacement of the product and Roman disclaims all liability for consequential damages. Conditions of use are beyond our control.

Roman Decorating Products • Calumet City, Illinois
Questions? Call 1-800-488-6117.
www.romandecoratingproducts.com

7/09

CAUTION

Do not freeze. Do not take internally. In case of ingestion, seek medical attention. Avoid contact with skin and eyes. Use of skin and eye protection is recommended at all times. If contact with eye occurs, flush with water for 15 minutes. If skin contact occurs, wash with soap and water. Seek medical attention if rash or other symptoms occur. Do not mix with other chemicals. Use in a well ventilated work area. Close container after each use. Keep out of reach of children.

