

Product Data Sheet

Kitchen & Bath, PRO-595

Product Numbers: 16101, 16112

Base: Synthetic Polymer

General Properties: Kitchen & Bath Wallpaper Adhesive, PRO-595, is designed specifically for hanging pre-pasted and unpasted wallpaper in the kitchen and bath. It is a ready-to-use adhesive guaranteed to perform in high humidity or mildew prone areas. It solves the most frequent problems in kitchens and baths-curling edges, lifting seams and mildew.

- For use with unpasted and pre-pasted wallpaper
- Maximum mildew protection
- Prevents curling and lifting seams
- Low VOC, LEED and VOC regulation compliant

Recommended Uses: For hanging pre-pasted and unpasted wallpaper in the kitchen or bath.

Not Recommended For: Hanging over existing wallpaper.

Substrates: Apply over ULTRA-PRIME®, PRO-977 Primer.

Non-Compatible Coatings: Teflon or Tedlar Type Surfaces



APPLICATION INSTRUCTIONS

Surface Preparation: Surface must be free from grease, mildew and other residues. Refer to www.epa.gov for instructions on removing mold. Surface should be dry, smooth and structurally sound. Check surface for paint bonding, damaged wallboard or plaster. Repair all unsound surfaces. Remove existing wallpaper: Score paper with PIRANHA™ Wallpaper Scoring Tool and apply PIRANHA™ Wallpaper Remover. Before proceeding with any unusual conditions, consult your adhesive or wallcovering supplier. To guarantee the success of Kitchen & Bath Wallpaper Adhesive, the surface must be primed with ROMAN'S ULTRA-PRIME® primer.

Tinting: N/A

Dilution: Do not dilute.

Application Method: Use only when the room temperature is above 50°F. It is highly recommended to work with one sheet at a time. Apply a thin, even coat with a roller or brush. Avoid contact with the surface of embossed or delicate wallpaper. Book according to wallcovering manufacturer's instructions.

Drying Time: Drying time will vary depending on the temperature and humidity of the room. Adhesive takes one week to cure before it attains its properties.

Clean-Up: Before the adhesive dries, remove excess with warm, clean water. Additional effort may be required if the adhesive is allowed to contact the surface of embossed or textured vinyls. The adhesive is more difficult to clean up when dry.

SPECIFICATION DATA

Percent Solids: Approximately 15%

Coverage: Approximately 250 square feet per gallon

Viscosity: Approximately 15,000 cps

VOC: Less than 240 grams/liter

Drying Time: Drying time will vary depending on the temperature and humidity of the room.

Storage: Avoid freezing; keep in cool, dry place.

LIMITED WARRANTY

Roman warrants that it will replace this product free of charge if within 24 months of manufacture it is found defective in material or workmanship. This warranty is in lieu of any other. The exclusive remedy is limited to the replacement of the product and Roman disclaims all liability for consequential damages. Conditions of use are beyond our control.

Roman Decorating Products • Calumet City, Illinois
Questions? Call 1-800-488-6117.
www.romandecoratingproducts.com

CAUTION

Do not freeze. Do not take internally. In case of ingestion, seek medical attention. Avoid contact with skin and eyes. Use of skin and eye protection is recommended at all times. If contact with eye occurs, flush with water for 15 minutes. If skin contact occurs, wash with soap and water. Seek medical attention if rash or other symptoms occur. Do not mix with other chemicals. Use in a well ventilated work area. Close container after each use. Keep out of reach of children.