

Product Data Sheet

ULTRA CLEAR™, PRO-880

Product Numbers: 12405, 12404, 12401, 12414

Base: Starch

General Properties: Premium clear, strippable adhesive which combines the best features of clays and clears. Excellent for the retail customer as well as the most discriminating contractor.

- Maximum Tack
- Extended Open Time
- Unsurpassed Ease of Clean Up
- Spreads and Flows easily
- Low VOC, LEED and VOC regulation compliant

Recommended Uses: For all weights of wallcoverings. Strippable when used with fabric backed vinyl over bare drywall with a cure time of 4-6 weeks.

Compatible Coatings: All ROMAN® primers

Substrates: Apply over new, bare drywall or over a ROMAN® primer.

Not Recommended For: Application over oil/alkyd primers or paints without use of a primer

SPECIFICATION DATA

Percent Solids: Approximately 32%

Coverage: Approximately 300 square feet per gallon

Viscosity: Approximately 40,000 - 45,000 cps

Drying Time: Drying time will vary depending on the temperature, ventilation and humidity of the room.

Storage: Avoid freezing; keep in cool, dry place.

LIMITED WARRANTY

Roman warrants that it will replace this product free of charge if within twelve months of manufacture it is found defective in material or workmanship. This warranty is in lieu of any other. The exclusive remedy is limited to the replacement of the product and Roman disclaims all liability for consequential damages. Conditions of use are beyond our control.

Roman Decorating Products • Calumet City, Illinois
Questions? Call 1-800-488-6117.



APPLICATION INSTRUCTIONS

Surface Preparation: Surface must be free from grease and other residues, dry, smooth and structurally sound. Check surfaces for paint bonding, loose wallcoverings, damaged wallboard or plaster. Repair all unsound surfaces. Prime all surfaces (including oil-based coatings) with ROMAN® ULTRA-PRIME®. Priming of bare drywall is not required with fabric-backed wallcoverings. Before proceeding with any unusual conditions, consult your adhesive or wallcovering supplier.

Tinting: N/A

Dilution: For use with pre-pasted wallcoverings, dilute with 1/2 gallon of water per gallon of adhesive. For some pasting machines, thin with maximum one pint of water per gallon.

Application Method: Use only when the room temperature is above 50F. Apply an even coat of adhesive with a pasting machine, brush or roller. Avoid contact with the surface of embossed, textured or delicate wallcoverings. Book according to the wallcovering manufacturer's instructions.

Drying Time: Varies depending on the temperature, ventilation and humidity of the room.

Clean-Up: Before the adhesive dries, remove the excess with clean water. Additional effort may be required if the adhesive is allowed to contact the surface of embossed or textured vinyls.

CAUTION

Do not freeze. Do not take internally. In case of ingestion, seek medical attention. Avoid contact with skin and eyes. Use of skin and eye protection is recommended at all times. If contact with eye occurs, flush with water for 15 minutes. If skin contact occurs, wash with soap and water. Seek medical attention if rash or other symptoms occur. Do not mix with other chemicals. Use in a well ventilated work area. Close container after each use. Keep out of reach of children.

Non-Compatible Coatings: Oil/alkyd paints or primers