

Product Data Sheet

ARMORSHIELD™

Base: 100% acrylic resin

General Properties: Roman's ARMORSHIELD™ is a interior water-based, high solids, highly flexible coating. It is designed for application on interior drywall, masonry, and other properly prepared surfaces where durability, abuse resistance and a decorative appearance are desired.

- Extremely Hard Finish
- Superior Flexibility
- Abuse Resistant
- Mold and Mildew Resistant
- Crack Resistant
- Scrub Resistant
- Permeable
- Easily Applied
- Tintable

Not Recommended For: Exterior surfaces

Substrates: Apply over new, bare drywall, cured plaster, paint, wood paneling or filling compounds.

SPECIFICATION DATA

85° Sheen: Range 10-15

Percent Solids: Approximately 50%

Coverage: Approximately 200-250 square feet per gallon at 8 mil wet thickness/6 mil dry

Viscosity: Approximately 5,000 cps

Drying Time: Drying time will vary depending on the temperature, ventilation and humidity of the room. Normally, less than one hour.

Storage: Avoid freezing; keep in cool, dry place.

LIMITED WARRANTY

Roman warrants that it will replace this product free of charge if within twelve months of manufacture it is found defective in material or workmanship. This warranty is in lieu of any other. The exclusive remedy is limited to the replacement of the product and Roman disclaims all liability for consequential damages. Conditions of use are beyond our control.

Roman Architectural Finishes • Calumet City, Illinois
Questions? Call 1-800-697-1823.
www.romanarchitecturalfinishes.com

3/08

APPLICATION INSTRUCTIONS

Surface Preparation: Surface must be free from grease and other residues, dry, smooth and structurally sound. Check surfaces for paint bonding, damaged wallboard or plaster. Repair all unsound surfaces.

Application Method: Use only when the room temperature is above 50°F. Apply an even coat of with a brush, roller, or spraying system. The airless spray system must be capable of spraying at 2000 PSI with a 1.5 GPM output.

Drying Time: ARMORSHIELD™ is dry and ready to hang over in less than one hour. Low temperature, high humidity and poor ventilation will slow down the drying process.

Clean-Up: Before ARMORSHIELD™ dries, remove the excess with clean water. Brushes and rollers should be cleaned immediately after use with warm, clean water.

CAUTION

Do not freeze. Do not take internally. In case of ingestion, seek medical attention. Avoid contact with skin and eyes. Use of skin and eye protection is recommended at all times. If contact with eye occurs, flush with water for 15 minutes. If skin contact occurs, wash with soap and water. Seek medical attention if rash or other symptoms occur. Do not mix with other chemicals. Use in a well ventilated work area. Close containers after each use. Keep out of reach of children.