

# Product Data Sheet

## GH-57 Universal Wallpaper Paste

**Product Numbers:** 209864, 209862, 209867, 209861

**Base:** Synthetic Polymer

**General Properties:** Universal Wallpaper Paste makes hanging wallpaper easy. This paste may be used on all surfaces except for poor quality latex paint.

- For all wallpaper
- Longer open time & more slip
- Maximum adhesion
- Eliminates messy water tray
- Hangs up to 4 double rolls
- Low VOC, LEED and VOC regulation compliant

**Recommended Uses:** For hanging over wallcovering or painted surfaces.

**Not Recommended For:** Bare Drywall, extremely rough surfaces such as concrete block, stucco, and other rough surfaces.

**Non-Compatible Coatings:** Teflon or Tedlar Type Surfaces

### SPECIFICATION DATA

**Percent Solids:** Approximately 14%

**Coverage:** Approx. 250 square feet per gallon

**Viscosity:** Approximately 14,000 cps

**Drying Time:** Drying time will vary depending on the temperature, ventilation and humidity of the room.

**Storage:** Avoid freezing; keep in cool, dry place.

### LIMITED WARRANTY

Golden Harvest warrants that it will replace this product free of charge if within 24 months of manufacture it is found defective in material or workmanship. This warranty is in lieu of any other. The exclusive remedy is limited to the replacement of the product and Golden Harvest disclaims all liability for consequential damages. Conditions of use are beyond our control.

Roman Decorating Products • Calumet City, Illinois  
Questions? Call 1-800-488-6117.  
[www.romandecoratingproducts.com](http://www.romandecoratingproducts.com)



### APPLICATION INSTRUCTIONS

**Surface Preparation:** Surface must be free from grease and other residues, dry, smooth and structurally sound. Check surfaces for loose wallcoverings. Repair all unsound surfaces. Before proceeding with any unusual conditions, consult your adhesive or wallcovering supplier. To check for poor quality latex paint, cut an "x" in the wall and apply clear tape over it. Remove quickly, if there is paint on the tape, you need to prime with a Roman® Primer.

**Tinting:** N/A

**Dilution:** Do not dilute.

**Application Method:** Use only when the room temperature is above 50°F. Apply an even coat covering the entire surface.

**Drying Time:** Drying time between two vinyls will vary depending on the temperature, ventilation and humidity of the room.

**Clean-Up:** Before the paste dries, remove excess with warm, clean water. Additional effort may be required if the paste is allowed to contact the surface of embossed or textured vinyls. Paste can be difficult to clean up after it is dry.

### CAUTION

Do not freeze. Do not take internally. In case of ingestion, seek medical attention. Avoid contact with skin and eyes. Use of skin and eye protection is recommended at all times. If contact with eye occurs, flush with water for 15 minutes. If skin contact occurs, wash with soap and water. Seek medical attention if rash or other symptoms occur. Do not mix with other chemicals. Use in a well ventilated work area. Close container after each use. Keep out of reach of children.