

Product Data Sheet


TEKNAbond®

Base: Cold water soluble starch

General Properties: TEKNAbond® is a multi-purpose product, it is the most recognized universal dry adhesive/sizer in the marketplace

- For all types of wallcoverings
- Excellent for pre-pasted papers

Compatible Coatings: All ROMAN/GOLDEN HARVEST® primers



LIMITED WARRANTY

GOLDEN HARVEST warrants that it will replace this product free of charge if within twelve months of manufacture it is found defective in material or workmanship. This warranty is in lieu of any other. The exclusive remedy is limited to the replacement of the product and GOLDEN HARVEST disclaims all liability for consequential damages. Conditions of use are beyond our control.

CAUTION

Do not freeze. Do not take internally. In case of ingestion, seek medical attention. Avoid contact with skin and eyes. Use of skin and eye protection is recommended at all times. If contact with eye occurs, flush with water for 15 minutes. If skin contact occurs, wash with soap and water. Seek medical attention if rash or other symptoms occur. Do not mix with other chemicals. Use in a well ventilated work area. Close container after each use. Keep out of reach of children.

Roman Decorating Products • Calumet City, Illinois
Questions? Call 1-800-488-6117.
www.romandecoratingproducts.com

APPLICATION INSTRUCTIONS

Surface Preparation: Surface must be free from grease and other residues, dry, smooth and structurally sound. Check surfaces for paint bonding, loose wallcoverings, damaged wallboard or plaster. Repair all unsound surfaces. Before proceeding with any unusual conditions, consult your adhesive or wallcovering supplier.

Mixing Instructions: Following chart below, slowly stir entire contents of package into cold water. Continue stirring for 30 seconds. Let stand for 10 minutes, stirring occasionally. Stir thoroughly before use.

8 oz.

<u>Wallcovering</u>	<u>Water</u>	<u>Coverage</u>
Sizing	16 pints	650 sq. ft.
Prepasted Paper	16 pints	14-16 rolls
Light Weight Papers/Vinyls	16 pints	12-14 rolls
Medium Weight Vinyls	12 pints	10-12 rolls
Grass, Silks, Strings and other Natural or Delicate Materials	10 pints	8-10 rolls

Application Method: Use only when the room temperature is above 50F. Apply paste evenly to back of wallcovering with clean 3/8" nap paint roller. Book by folding each strip onto itself, paste side in. Set aside for 3-5 minutes. Hang strips by pressing air pockets and excess paste from center outward toward seams. Avoid contact with the surface of embossed, textured or delicate wallcoverings. Book according to the wallcovering manufacturer's instructions.

Clean-Up: Before the adhesive dries, remove the excess with clean water. Additional effort may be required if the adhesive is allowed to contact the surface of embossed or textured vinyls.